STATE OF CALIFORNIA—ENVIRONMENTAL PROTECTION AGENCY PETE WILSON, *Governor*

CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
LOS ANGELES REGION
101 CENTRE PLAZA DRIVE
MONTEREY PARK, CA 91754-2156
(213) 266-7500
FAX: (213) 266-7600

January 12, 1996

Robert Griffin
UTILITY TRAILER MANUFACTURING CO.
17300 E. chestnut Street, P.O. Box 1299
City of Industry, CA 91749-1299

WELL INVESTIGATION PROGRAM - WORK PLAN, UTILITY TRAILER MANUFACTURING CO., 17300 E. CHESTNUT STREET, CITY OF INDUSTRY (FILE No. 105.0296)

We have received the "Soil Stockpile Treatment, Sampling and Reuse Plan", prepared by your consultant, Harding Lawson Associates, dated November 2, 1995 (received on November 6, 1995). This submission presents results of confirmation soil sample analysis and a proposal for on-site disposal of treated soil.

Approximately 250 cubic yards of VOC contaminated soil was stockpiled and treated on-site using vapor extraction methods. Upon completion of treatment, ten representative soil samples were collected and analyzed for VOCs. Only two of the soil samples contained traces of VOCs that exceeded detection limits. Based on these results, the subject submission proposes to reuse the soil as on-site construction backfill.

Board staff have no objections to reuse of the stockpiled soil as backfill on the subject site. The traces of VOCs detected in the confirmation samples will either dissipate during backfilling or soon after by natural degradation. An effort should be made to place the VOC-tainted portion of the stockpiled soil in the upper portion of the backfill to further reduce the possibility of ground water degradation. Considering the depth to ground water and presence of clayey interbeds in the soil beneath the site, the VOC levels detected in the stockpiled soil are within allowable limits based on our recently issued Site Assessment and Cleanup Guidebook.

Please contact Walter Salas at (213) 266-7542 or John Lewis at (213) 266-7552 if you have any questions, and address all correspondence to Walter Salas attention.

ERIC NUPEN, R.G.
Senior Engineering Geologist

Wheelabrator Clean Air Systems Inc.

2130 Leo Avenue
Los Angeles, CA 90040
Tel 213-722-7500
Fax. 213-722-8207

ANALYTICAL REPORT

Customer: Utility Trailer	Lab I.D. #: 5557
Project:	Date Reported: 07/17/95
Address : City of Industry California	Date Sampled: 07/03/95
	Date Received: 07/05/95
Attention: c/o Mr. Mark Bailey	Date Analyzed: 07/14/95
Sample Matrix: Granular Activated Carbon	Date Extracted: 07/07/95

TCLP VOLATILES BY EPA 601/602
PURGEABLE ORGANICS

compound	cas #	concentration (mg/L)	limit of detection (mg/L)	TCLP limits (mg/L)
Vinyl Chloride	75-01-4	<0.03	0.03	0.2
1,1-Dichloroethene 1,1DCE	75-35-4	0.03	0.01	0.7
Chloroform	67-66-3	<0.01	0.01	6.0
1,2-Dichloroethane	107-06-2	<0.01	0.01	0.5
2-Butanone	78-93-3	<0.50	0.50	200
Carbon Tetrachloride	56-23-5	<0.01	0.01	0.5
Trichloroethene TCE	79-01-6	0.03	0.01	0.5
Benzene	71-43-2	<0.01	0.01	0.5
Tetrachloroethene PCE	127-18-4	0.13	0.01	0.7
Chlorobenzene	108-90-7	<0.01	0.01	100

The volatile organic analyses was extracted using a Zero Headspace Toxicity Characteristic Leaching Procedure (TCLP). The leachate was prepared according to the procedure as listed in the 49CFR March 29 and June 29 1990 Federal Registers.

A sample is considered to have failed the volatile TCLP test and is considered a hazardous waste if any of the volatile compounds exceed the maxima limits as listed in the last column. These limits have been taken from the March 29, Federal Register , pp 11845-6.

Respectfully submitted,

Dr. James R. Graham, Ph.D
Technical Director

Post-it™ Fax Note 7671	Date 1/18/96 # of pages ▶ 1
To BOB GRUFFIS	From KEVIN TROUT
Co./Dept. UTM	Co. HLA
Phone #	Phone #
Fax # 818 965-2790	Fax #

UTM 005494

This report is submitted in confidence to the above named client. Authorization for publication of this report, conclusions, or extracts from or regarding it is restricted without written approval of Westates Carbon, Inc. as a mutual protection to our clients, the public and ourselves.